Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1.   (Currently Amended) An electro-optical device, comprising:

a plurality of scanning lines;

a plurality of data lines;

a plurality of electro-optical elements; and

a plurality of pixel circuits to drive the plurality of electro-optical elements, each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, and a reset transistor to reset the data signal stored in the storage capacitor,

brightness of each of the electro-optical elements being set for each of a plurality of sub-frames based on the data signal stored in the storage capacitor, which constitute one frame of a period and each have a predetermined period, so that at least two levels of brightness can be set for one frame;

a sub-frame having a longest period among the plurality of sub-frames being divided into at least two allocated sub-frames, and

the plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.

2.   (Previously Presented) The electro-optical device according to Claim 1,

a sum of the period of the at least two allocated sub-frames being set to 2^n times as long as a sub-frame having a shortest period among n (n denotes a natural number)

sub-frames of the plurality of sub-frames, wherein n is a number of sub-frames excluding the

at least two allocated sub-frames.

3.　　(Previously Presented)　The electro-optical device according to Claim 2,

a sub-frame having a longest period among the plurality of sub-frames,

excluding the at least two allocated sub-frames, being half as long as the sub-frame having the

longest period among the plurality of sub-frames.

4.　　(Previously Presented)　The electro-optical device according to Claim 1,

the two allocated sub-frames not being arranged consecutively in one frame of

a period.

5.　　(Currently Amended)　An electro-optical device, comprising:

a plurality of scanning lines;

a plurality of data lines;

a plurality of electro-optical elements; and

a plurality of pixel circuits to drive the plurality of electro-optical elements,

each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a

data signal supplied via a data line among the plurality of data lines and the first transistor,

and a reset transistor to reset the data signal stored in the storage capacitor,

brightness of the electro-optical element being set for each of a plurality of

sub-frames based on the data signal stored in the storage capacitor, which constitute one

frame of a period and each have a predetermined period, so that at least two levels of

brightness can be set for one frame, and lengths of the plurality of sub-frames excluding a

sub-frame having a longest period being set to a period in binary weighted;

the sub-frame having the longest period among the plurality of sub-frames

being divided into at least two allocated sub-frames, and

the plurality of sub-frames, which are set for a series of electro-optical

elements among the plurality of electro-optical elements, the series of electro-optical elements

being connected to at least two scanning lines, <u>and one of two scanning lines being connected</u>

<u>to the reset transistor,</u> end substantially simultaneously <u>based on a reset signal supplied to the</u>

<u>reset transistor via the scanning line.</u>

6.   (Previously Presented) The electro-optical device according to Claim 5,

the two allocated sub-frames not being arranged consecutively in one frame of

a period.

7.   (Currently Amended) An electro-optical device, comprising:

a plurality of scanning lines;

a plurality of data lines;

a plurality of electro-optical elements; and

a plurality of pixel circuits to drive the plurality of electro-optical elements,

each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a

data signal supplied via a data line among the plurality of data lines and the first transistor,

<u>and a reset transistor to reset the data signal stored in the storage capacitor,</u>

brightness of the electro-optical element being set for each of a plurality of

sub-frames, which constitute one frame of a period and each have a predetermined period,

a sub-frame having a longest period among the plurality of sub-frames being

divided into at least two allocated sub-frames, and

a sub-frame having a longest period among n (n denotes a natural number)

sub-frames of the plurality of sub-frames, excluding the at least two allocated sub-frames,

being set to 2^{n-1} times as long as a sub-frame having a shortest period among the n sub-

frames,

brightness for the one frame can be set to 2^{n+1} levels, and

-4-

the plurality of sub-frames, which are set for a series of electro-optical

elements among the plurality of electro-optical elements, the series of electro-optical elements

being connected to at least two scanning lines, and one of two scanning lines being connected

to the reset transistor end substantially simultaneously based on a reset signal supplied to the

reset transistor via the scanning line.

8.   (Previously Presented) The electro-optical device according to Claim 7,

the two allocated sub-frames not being arranged consecutively in one frame of

a period.

9-10.   (Canceled)

11.   (Currently Amended) An electro-optical device, comprising:

a plurality of scanning lines;

a plurality of data lines;

a plurality of electro-optical elements; and

a plurality of pixel circuits to drive the plurality of electro-optical elements,

each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a

data signal supplied via a data line among the plurality of data lines and the first transistor,

and a reset transistor to reset the data signal stored in the storage capacitor,

brightness of the electro-optical element being set for each of a plurality of

sub-frames, which constitute one frame of a period and each have a predetermined period, so

that at least 2^n (n denotes a natural number) levels of brightness can be set for one frame,

a number of the plurality of sub-frames being n + 1 or more,

a sub-frame having a longest period among the plurality of sub-frames being

divided into at least two allocated sub-frames, and

the plurality of sub-frames, which are set for a series of electro-optical

elements among the plurality of electro-optical elements, the series of electro-optical elements

being connected to at least two scanning lines, and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line. ~~end substantially simultaneously.~~

12. (Previously Presented) The electro-optical device according to Claim 11, a sub-frame having a longest period among the plurality of sub-frames, excluding the at least two allocated sub-frames, being 2^{n-1} times as long as a sub-frame having a shortest period.

13. (Currently Amended) An electro-optical device, which is capable of setting at least two levels of brightness for one frame, the electro-optical device comprising:

a plurality of scanning lines;

a plurality of data lines;

a plurality of electro-optical elements; and

a plurality of pixel circuits to drive the plurality of electro-optical elements, each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, and a reset transistor to reset the data signal stored in the storage capacitor,

electro-optical elements that are controlled to take either an ON state or an OFF state based on gray scale data for each of a plurality of sub-frames, which constitute one frame of a period and each have a predetermined period, and at least two of the plurality of sub-frames being controlled to always concurrently take either the ON state or the OFF state;

a sub-frame having a longest period among the plurality of sub-frames being divided into at least two allocated sub-frames, and

the plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, and one of two scanning lines being connected

to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.end substantially simultaneously.

14.   (Previously Presented) The electro-optical device according to Claim 13, the at least two allocated sub-frames having the same period of length.

15.   (Previously Presented) The electro-optical device according to Claim 13, the at least two allocated sub-frames not being arranged consecutively in one frame of a period.

16-19. (Canceled)

20.   (Previously Presented) The electro-optical device according to Claim 1, the electro-optical elements being an EL element.

21.   (Original) The electro-optical device according to Claim 20, the EL element having a light-emitting layer formed of an organic material.

22.   (Currently Amended) A method of driving an electro-optical device that includes a plurality of scanning lines; a plurality of data lines; a plurality of electro-optical elements; and a plurality of pixel circuits to drive the plurality of electro-optical elements, each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, and a reset transistor to reset the data signal stored in the storage capacitor, the method comprising:

setting brightness of the electro-optical element for each of a plurality of sub-frames based on the data signal stored in the storage capacitor, which constitute one frame of period and each have a predetermined period, so that at least two levels of brightness can be set for one frame,

dividing a sub-frame having a longest period among the plurality of sub-frames into at least two allocated sub-frames, and

setting a plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, <u>and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.</u><s>end substantially simultaneously.</s>

23.   (Currently Amended) A method of driving an electro-optical device that includes a plurality of scanning lines; a plurality of data lines; a plurality of electro-optical elements; and a plurality of pixel circuits to drive the plurality of electro-optical elements, each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, <u>and a reset transistor to reset the data signal stored in the storage capacitor,</u> the method comprising:

setting brightness of the electro-optical elements for each of a plurality of sub-frames based on the data signal stored in the storage capacitor, which constitute one frame of period and each have a predetermined period, so that at least two levels of brightness can be set for one frame, lengths of the plurality of sub-frames excluding a sub-frame having a longest period being set in binary load,

dividing the sub-frame having the longest period among the plurality of sub-frames into at least two allocated sub-frames, and

setting a plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, <u>and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.</u><s>ending substantially simultaneously.</s>

24.   (Currently Amended) A method of driving an electro-optical device that includes a plurality of scanning lines; a plurality of data lines; a plurality of electro-optical elements; and a plurality of pixel circuits to drive the plurality of electro-optical elements, each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, and a reset transistor to reset the data signal stored in the storage capacitor, the method comprising:

setting brightness of the electro-optical elements for each of a plurality of sub-frames based on the data signal stored in the storage capacitor, which constitute one frame of period and each have a predetermined period,

dividing a sub-frame having a longest period among the plurality of sub-frames into at least two allocated sub-frames,

setting a sub-frame having a longest period among n (n denotes a natural number) sub-frames of the plurality of sub-frames, excluding the at least two allocated sub-frames, to 2^{n-1} times as long as a sub-frame having a shortest period of the n sub-frames,

setting brightness for one frame to 2^{n+1} levels, and

setting a plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.end substantially simultaneously.

25.   (Canceled)

26.   (Currently Amended) A method of driving an electro-optical device that includes a plurality of scanning lines; a plurality of data lines; a plurality of electro-optical elements; and a plurality of pixel circuits to drive the plurality of electro-optical elements,

each of the plurality of pixel circuits having a first transistor and a storage capacitor to store a data signal supplied via a data line among the plurality of data lines and the first transistor, and a reset transistor to reset the data signal stored in the storage capacitor, the method comprising:

setting brightness of the electro-optical element for each of a plurality of sub-frames based on the data signal stored in the storage capacitor, which constitute one frame of a period and each have a predetermined period, so that at least 2^n (n denotes a natural number) levels of brightness are set for one frame with the number of the plurality of sub-frames being n + 1 or more,

dividing a sub-frame having a longest period among the plurality of sub-frames into at least two allocated sub-frames,

always concurrently putting the at least two allocated sub-frames into a set state or a non-set state,

setting brightness for one frame to 2^n levels, and

setting a plurality of sub-frames, which are set for a series of electro-optical elements among the plurality of electro-optical elements, the series of electro-optical elements being connected to at least two scanning lines, and one of two scanning lines being connected to the reset transistor, end substantially simultaneously based on a reset signal supplied to the reset transistor via the scanning line.end substantially simultaneously.

27-29. (Canceled)

30.   (Original) An electronic apparatus, comprising:

the electro-optical device according to Claim 1.